Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



SERIE 180X

250XB

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 60mm ean 23392

Material: Non-marking Rubber tyre

Polypropylene

Application field:

Industry

Description:

Wheel with synthetic rubber tread and thermoplastic rim. Thread guards made of pressed stainless steel AISI 304 or thermoplastic material.

Furniture Castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem and locking device to stop both wheel and rotation.

Product line: Stainless steel

EAN13:8018793233927 **EAN5**:23392

Article code:22250B0060X5G



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 50 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 85

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware
- Wood

Wheel data

Diameter (mm)	60
Band width (mm)	23
Hub width (mm)	29
Hub version	Plain bore
Wheel hole (mm)	8
Bearing seat (mm)	1
Dynamic load capacity (DaN)	50
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	27
Ground clearance (mm)	88
Castor hole (mm)	1
Static load capacity (DaN)	70
Structure	Swivel
Version	Axle
Brake	1
Plain axle	10X30
Stem type	Threaded axle
Finishing	AISI 304 stainless steel