

SERIE 180X

## 250XB

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 60mm ean 23392

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Industry

**Description:**

Wheel with synthetic rubber tread and thermoplastic rim. Thread guards made of pressed stainless steel AISI 304 or thermoplastic material. Hub on plain bore.

**Furniture Castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem.

**Product line:** Stainless steel

**EAN13:**8018793233927 **EAN5:**23392 **Article code:**22250B0060X5G



## Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 50 DaN  
**Rotation:** Plain bore **Hardness scale:** Shore A **Hardness:** 85

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware
- Wood

## Wheel data

Diameter (mm)	60
Band width (mm)	23
Hub width (mm)	29
Hub version	Plain bore
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	50
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	27
Ground clearance (mm)	88
Castor hole (mm)	/
Static load capacity (DaN)	70
Structure	Swivel
Version	Axle
Brake	/
Plain axle	10X30
Stem type	Threaded axle
Finishing	AISI 304 stainless steel