

SERIE 180X

250XBIS

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 60mm ean 25942

Material: Non-marking
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with synthetic rubber tread and thermoplastic rim. Thread guards made of pressed stainless steel AISI 304 or thermoplastic material. Hub on plain bore.

Furniture Castors:

Made of pressed steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate, front brake and locking device to stop both wheel and rotation.

Product line: Stainless steel

EAN13:8018793259422 **EAN5:**25942 **Article code:**222500F060XOG



Features

Minimum temperature: -20 **Maximum temperature:** 80 **Dynamic load capacity:** 50 DaN
Rotation: Plain bore **Hardness scale:** Shore A **Hardness:** 85

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware
- Wood

Wheel data

Diameter (mm)	60
Band width (mm)	23
Hub width (mm)	29
Hub version	Plain bore
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	50
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	060X060
Plate hole spacing (mm)	042X042
Plate hole size (mm)	6,5X10
Offset (mm)	27
Ground clearance (mm)	88
Castor hole (mm)	/
Static load capacity (DaN)	70
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel