

SERIE 139L

## 140LXANTF

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 75mm ean 23138

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Industry

**Description:**

Wheel with grey non-marking rubber tyre 85 Shore A and thermoplastic material centre. Hub on central ball bearing with threadguards.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole and front brake. Dust cover ring on the balls.

**Product line:** Rubber tyre, Stainless steel

**EAN13:**8018793231381

**EAN5:**23138

**Article code:**06140FA075LCX



## Features

**Minimum temperature:** -20

**Maximum temperature:** 60

**Dynamic load capacity:** 100 DaN

**Rotation:** Stainless steel ball bearing

**Hardness scale:** Shore A

**Hardness:** 85

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                              |
|-----------------------------|------------------------------|
| Diameter (mm)               | 75                           |
| Band width (mm)             | 28                           |
| Hub width (mm)              | 40                           |
| Hub version                 | Stainless steel ball bearing |
| Wheel hole (mm)             | 8                            |
| Bearing seat (mm)           | /                            |
| Dynamic load capacity (DaN) | 100                          |
| Colour                      | Grey                         |
| Material                    | Non-marking Rubber tyre      |
| Box pieces                  | /                            |
| Hardness scale              | Shore A                      |
| Hardness                    | 85                           |

## Support data

|                            |                          |
|----------------------------|--------------------------|
| Plate size (mm)            | /                        |
| Plate hole spacing (mm)    | /                        |
| Plate hole size (mm)       | /                        |
| Offset (mm)                | 40                       |
| Ground clearance (mm)      | 103                      |
| Castor hole (mm)           | 12                       |
| Static load capacity (DaN) | 120                      |
| Structure                  | Swivel                   |
| Version                    | Bolt hole with brake     |
| Brake                      | Front                    |
| Plain axle                 | /                        |
| Stem type                  | /                        |
| Finishing                  | AISI 304 stainless steel |