

SERIE 139

140X

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 75mm ean 24178

Material: Non-marking
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with grey non-marking rubber tyre 85 Shore A and thermoplastic material centre. Hub on plain bore.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate. Dust cover ring on the balls.

Product line: Stainless steel, Rubber tyre

EAN13:8018793241786 **EAN5:**24178 **Article code:**0614000075LFX



Features

Minimum temperature: -20

Maximum temperature: 60

Dynamic load capacity: 75 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 85

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|-------------------------|
| Diameter (mm) | 75 |
| Band width (mm) | 28 |
| Hub width (mm) | 40 |
| Hub version | Plain bore |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 75 |
| Colour | Grey |
| Material | Non-marking Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 85 |

Support data

| | |
|----------------------------|--------------------------|
| Plate size (mm) | 100X085 |
| Plate hole spacing (mm) | 080X060 |
| Plate hole size (mm) | 8,5X12 |
| Offset (mm) | 40 |
| Ground clearance (mm) | 105 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 95 |
| Structure | Swivel |
| Version | Plate |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | AISI 304 stainless steel |