

SERIE 180X

## 250XF

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 75mm ean 27963

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Industry

**Description:**

Wheel with synthetic rubber tread and thermoplastic rim. Thread guards made of pressed stainless steel AISI 304 or thermoplastic material. Hub on plain bore.

**Furniture Castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole and locking device to stop both wheel and rotation.

**Product line:** Stainless steel

**EAN13:**8018793279635 **EAN5:**27963 **Article code:**22250F0075X0G



## Features

**Minimum temperature:** -20 **Maximum temperature:** 80 **Dynamic load capacity:** 55 DaN  
**Rotation:** Plain bore **Hardness scale:** Shore A **Hardness:** 85

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware
- Wood

## Wheel data

Diameter (mm)	75
Band width (mm)	23
Hub width (mm)	29
Hub version	Plain bore
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	55
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	30
Ground clearance (mm)	103
Castor hole (mm)	10
Static load capacity (DaN)	75
Structure	Swivel
Version	Bolt hole
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel