Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 112B-AM

90XANTB

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 80mm ean 16587

Material: Non-marking Rubber tyre

Polypropylene

Application field:

Industry

Description:

Wheel with grey non-marking rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem and front brake. Dust cover ring on the balls.

Product line: Rubber tyre, Stainless steel

EAN13:8018793165877 **EAN5**:16587

:16587 **Article code**:02090XBA080BG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 50 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 83

Flooring

- Asphalt
- ConcreteStoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	1
Dynamic load capacity (DaN)	50
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	83

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	37
Ground clearance (mm)	105
Castor hole (mm)	1
Static load capacity (DaN)	70
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	AISI 304 stainless steel