

SERIE 112B-AM

90XB

AVO - Wheel with non-marking rubber tyre and aisi 304 stainless steel castor for industry, diameter 80mm ean 17435

Material: Non-marking
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with grey non-marking rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with stem. Dust cover ring on the balls.

Product line: Rubber tyre, Stainless steel

EAN13:8018793174350 **EAN5:**17435 **Article code:**02090XB0800BG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 50 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 83

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	50
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	105
Castor hole (mm)	/
Static load capacity (DaN)	70
Structure	Swivel
Version	Axle
Brake	/
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	AISI 304 stainless steel