

SERIE 180X

250XF

AVO - Wheel made of non-marking rubber tyre with aisi 304 stainless steel castor for industry, diameter 80mm ean 23395

Material: Non-marking Rubber tyre

Core: Polypropylene

Scope: Industry

Description:

Wheel with synthetic rubber tread and thermoplastic rim. Thread guards made of pressed stainless steel AISI 304 or thermoplastic material.

Furniture Castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420, with bolt hole and locking device to stop both wheel and rotation.

Product line: Stainless steel

EAN13:8018793233958

EAN5:23395

Article code:22250F0080X0G



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 55 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 85

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware
- Wood

Wheel data

| | |
|-----------------------------|-------------------------|
| Diameter (mm) | 80 |
| Band width (mm) | 23 |
| Hub width (mm) | 29 |
| Hub version | Plain bore |
| Wheel hole (mm) | 8 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 55 |
| Colour | Grey |
| Material | Non-marking Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 85 |

Support data

| | |
|----------------------------|--------------------------|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 30 |
| Ground clearance (mm) | 108 |
| Castor hole (mm) | 12 |
| Static load capacity (DaN) | 75 |
| Structure | Swivel |
| Version | Bolt hole |
| Brake | / |
| Plain axle | / |
| Stem type | / |
| Finishing | AISI 304 stainless steel |