

SERIE 16NX

366X

AVO - Wheel with non-marking rubber tyre with aisi 316 stainless steel castor for industry, diameter 80mm ean 24618

Material: / **Core:** Polyamide 6 **Scope:** Industry

Description:


Blue elastic cut-resistant rubber wheel 68 Shore A with black polyamide 6 centre. Hub on stainless steel roller bearings.

Medium duty castors:

In pressed stainless steel AISI 304 turning on double rim of balls in stainless steel AISI 420. Available in stainless steel AISI 316 for diameters mm. 80 and mm.100. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Stainless steel

EAN13:8018793246187 **EAN5:**24618 **Article code:**0X36600081NRG



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 120 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Stoneware
- Wood

Wheel data

Diameter (mm)	80
Band width (mm)	36
Hub width (mm)	40
Hub version	Stainless steel roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	120
Colour	Grey
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	107
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Aisi 316 stainless steel