

SERIE 16NX-AM

366XANTF

AVO - Wheels with rubber anti-stain with castor aisi 316 stainless steel for industry, diameter 80mm ean 24759

Material: / **Core:** Polyamide 6 **Scope:** Industry

Description:

Wheel with elastic no-marking rubber tyre 68 Shore A and Polyamide 6 centre. Hub on stainless steel roller bearing, shielded stainless steel ball bearings assembled with central spacer.

Medium duty castors:

In pressed stainless steel AISI 304 turning on double rim of balls in stainless steel AISI 420. Available in stainless steel AISI 316 for diameters mm. 80 and mm.100. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Stainless steel

EAN13:8018793247597 **EAN5:**24759 **Article code:**0X366FA081NRG

Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 120 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Stoneware
- Wood

Wheel data

Diameter (mm)	80
Band width (mm)	36
Hub width (mm)	40
Hub version	Stainless steel roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	120
Colour	Grey
Material	/
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	107
Castor hole (mm)	12
Static load capacity (DaN)	150
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Aisi 316 stainless steel