

SERIE 112AM

80A-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 100mm ean 29365

Material: Non-marking Rubber tyre

Core: Steel

Application field: Industry

Description:

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

In zinc-chromium plated pressed steel, fixed. Assembled with self locking nut.

Product line: Rubber tyre

EAN13:8018793293655 **EAN5:**29365 **Article code:**01080A01000RG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 70 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	70
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	/
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	90
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized