

SERIE 112B-AM

90-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 100mm ean 13184

Material: Non-marking
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with grey non-marking rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Rubber tyre, Stainless steel

EAN13:8018793131841

EAN5:13184

Article code:02090001000BG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 70 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 83

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	70
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	90
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized