

SERIE 112B-AM

## 90F-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 100mm ean 18029

**Material:** Non-marking Rubber tyre

**Core:** Polypropylene

**Application field:** Industry

**Description:**

Wheel with grey non-marking rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole. Assembled with self-locking nut.

**Product line:** Stainless steel, Rubber tyre

**EAN13:**8018793180290 **EAN5:**18029 **Article code:**020900F1001BG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 70 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 83

### Flooring

- Asphalt
- Concrete
- Stoneware

### Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 100                     |
| Band width (mm)             | 30                      |
| Hub width (mm)              | 40                      |
| Hub version                 | Plain bore              |
| Wheel hole (mm)             | 12                      |
| Bearing seat (mm)           | /                       |
| Dynamic load capacity (DaN) | 70                      |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | /                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 83                      |

### Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | /          |
| Plate hole spacing (mm)    | /          |
| Plate hole size (mm)       | /          |
| Offset (mm)                | 37         |
| Ground clearance (mm)      | 126        |
| Castor hole (mm)           | 12         |
| Static load capacity (DaN) | 90         |
| Structure                  | Swivel     |
| Version                    | Bolt hole  |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |