

SERIE 112AM

## 80BIS-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 100mm ean 19563

**Material:** Non-marking Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

**Medium duty castors:**

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

**Product line:** Rubber tyre

**EAN13:**8018793195638

**EAN5:**19563

**Article code:**01080F01000CG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 70 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 80

### Flooring

- Asphalt
- Concrete
- Stoneware

### Wheel data

Diameter (mm)	100
Band width (mm)	30
Hub width (mm)	37
Hub version	Ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	70
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

### Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	90
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized