Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 139L

# 140LB

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 100mm ean 24406

**Material:** Non-marking Rubber tyre

Polypropylene

Application field:

lene Industry

Description:

Wheel with grey non-marking rubber tyre 85 Shore A and thermoplastic material centre. Hub on central ball bearing with threadguards.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Rubber tyre, Stainless steel

**EAN13**:8018793244060 **EAN5**:24406 **Article code**:06140B3100LCG



#### **Features**

Minimum temperature: -20

Maximum temperature: 60

Dynamic load capacity: 100 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 85

## **Flooring**

- Asphalt
- ConcreteStoneware

### Wheel data

Diameter (mm)	100
Band width (mm)	32
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	1
Dynamic load capacity (DaN)	100
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	85

### Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	37
Ground clearance (mm)	152
Castor hole (mm)	1
Static load capacity (DaN)	120
Structure	Swivel
Version	Axle
Brake	1
Plain axle	12X30
Stem type	Threaded axle
Finishing	Galvanized