

SERIE 112AM

## 80BIS-AM

**AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 125mm**

**Material:** Non-marking Rubber tyre

**Core:** Steel

**Application field:** Industry

**Description:**

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

**Medium duty castors:**

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

**Product line:** Rubber tyre

**EAN13:/**    **EAN5:/**    **Article code:**01080F01250CG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 100 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 80

### Flooring

- Asphalt
- Concrete
- Stoneware

### Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 125                     |
| Band width (mm)             | 38                      |
| Hub width (mm)              | 46                      |
| Hub version                 | Ball bearing            |
| Wheel hole (mm)             | 10                      |
| Bearing seat (mm)           | /                       |
| Dynamic load capacity (DaN) | 100                     |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | /                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 80                      |

### Support data

|                            |                  |
|----------------------------|------------------|
| Plate size (mm)            | 100X085          |
| Plate hole spacing (mm)    | 080X060          |
| Plate hole size (mm)       | 8,5X12           |
| Offset (mm)                | 42               |
| Ground clearance (mm)      | 155              |
| Castor hole (mm)           | /                |
| Static load capacity (DaN) | 130              |
| Structure                  | Swivel           |
| Version                    | Plate with brake |
| Brake                      | Rear             |
| Plain axle                 | /                |
| Stem type                  | /                |
| Finishing                  | Galvanized       |