

SERIE 112AM

80B-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 125mm

Material: Non-marking Rubber tyre

Core: Steel

Application field: Industry

Description:

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Rubber tyre

EAN13:/ **EAN5:/** **Article code:**01080B21250RG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 100 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	38
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	45
Ground clearance (mm)	150
Castor hole (mm)	/
Static load capacity (DaN)	130
Structure	Swivel
Version	Axle
Brake	/
Plain axle	10X30
Stem type	Threaded axle
Finishing	Galvanized