

SERIE 112AM

## 80BISB-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 125mm

**Material:** Non-marking Rubber tyre    **Core:** Steel    **Scope:** Industry

**Description:**

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:/    EAN5:/    Article code:**01080BF1250RG



### Features

**Minimum temperature:** -20    **Maximum temperature:** 80    **Dynamic load capacity:** 100 DaN  
**Rotation:** Roller bearing    **Hardness scale:** Shore A    **Hardness:** 80

### Flooring

- Asphalt
- Concrete
- Stoneware

### Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 125                     |
| Band width (mm)             | 38                      |
| Hub width (mm)              | 50                      |
| Hub version                 | Roller bearing          |
| Wheel hole (mm)             | 15                      |
| Bearing seat (mm)           | /                       |
| Dynamic load capacity (DaN) | 100                     |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | /                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 80                      |

### Support data

|                            |   |
|----------------------------|---|
| Plate size (mm)            | /   |
| Plate hole spacing (mm)    | /   |
| Plate hole size (mm)       | /   |
| Offset (mm)                | 42  |
| Ground clearance (mm)      | 150                                       |
| Castor hole (mm)           | /   |
| Static load capacity (DaN) | 130                                       |
| Structure                  | Swivel                                    |
| Version                    | Axle with brake                           |
| Brake                      | Rear                                      |
| Plain axle                 | 22X50                                     |
| Stem type                  | Plain axle Stem(on request threaded stem) |
| Finishing                  | Galvanized                                |