

SERIE 16N-AM

66B-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 125mm ean 18337

Material: Non-marking
Rubber tyre

Core: Polyamide
6

Application field:
Industry

Description:

Wheel with elastic grey non-marking rubber tyre 68 Shore A and Polyamide 6 centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793183376

EAN5:18337

Article code:00066B0126NCG



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 170 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	36
Hub width (mm)	48
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	35X11
Dynamic load capacity (DaN)	170
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	42
Ground clearance (mm)	150
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Axle
Brake	/
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized