

SERIE 112B-AM

## 90ANTB-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 125mm ean 19264

**Material:** Non-marking Rubber tyre

**Core:** Polypropylene

**Scope:** Industry

**Description:**

Wheel with grey no-marking rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

**Product line:** Rubber tyre, Stainless steel

**EAN13:**8018793192644

**EAN5:**19264

**Article code:**02090SBA125RG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 100 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 83

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

Diameter (mm)	125
Band width (mm)	38
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	100
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	42
Ground clearance (mm)	152
Castor hole (mm)	/
Static load capacity (DaN)	130
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized