

SERIE 16N-AM

## 66ANTB-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 125mm ean 20761

**Material:** Non-marking  
Rubber tyre

**Core:** Polyamide  
6

**Application field:**  
Industry

**Description:**

Wheel with elastic grey non-marking rubber tyre 68 Shore A and Polyamide 6 centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793207614    **EAN5:**20761    **Article code:**00S66BA126NCG



### Features

**Minimum temperature:** -20    **Maximum temperature:** 70    **Dynamic load capacity:** 130 DaN  
**Rotation:** Ball bearing    **Hardness scale:** Shore A    **Hardness:** 68

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

<b>Diameter (mm)</b>	125
<b>Band width (mm)</b>	36
<b>Hub width (mm)</b>	48
<b>Hub version</b>	Ball bearing
<b>Wheel hole (mm)</b>	15
<b>Bearing seat (mm)</b>	/
<b>Dynamic load capacity (DaN)</b>	130
<b>Colour</b>	Grey
<b>Material</b>	Non-marking Rubber tyre
<b>Box pieces</b>	/
<b>Hardness scale</b>	Shore A
<b>Hardness</b>	68

### Support data

<b>Plate size (mm)</b>	/
<b>Plate hole spacing (mm)</b>	/
<b>Plate hole size (mm)</b>	/
<b>Offset (mm)</b>	42
<b>Ground clearance (mm)</b>	150
<b>Castor hole (mm)</b>	/
<b>Static load capacity (DaN)</b>	170
<b>Structure</b>	Swivel
<b>Version</b>	Axle with brake
<b>Brake</b>	Front
<b>Plain axle</b>	22X50
<b>Stem type</b>	Stem(on request threaded stem) Plain axle
<b>Finishing</b>	Galvanized