

SERIE 139L

140L

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 125mm ean 22916

Material: Non-marking Rubber tyre

Core: Polypropylene

Scope: Industry

Description:

Wheel with non-marking grey rubber tyre 85 Shore A and thermoplastic material centre. Hub on central ball bearing with threadguards.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Rubber tyre, Stainless steel

EAN13: 8018793229166

EAN5: 22916

Article code: 0614000125LCG



Features

Minimum temperature: -20

Maximum temperature: 60

Dynamic load capacity: 105 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 85

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	125
Band width (mm)	32
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	105
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	154
Castor hole (mm)	/
Static load capacity (DaN)	125
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized