

SERIE 139L

# 140LB

**AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 125mm ean 24942**

**Material:** Non-marking Rubber tyre

**Core:** Polypropylene

**Scope:** Industry

**Description:**

Wheel with non-marking grey rubber tyre 85 Shore A and thermoplastic material centre. Hub on central ball bearing with threadguards.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Rubber tyre, Stainless steel

**EAN13:**8018793249423

**EAN5:**24942

**Article code:**06140B3125LCG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 60

**Dynamic load capacity:** 105 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 85

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

Diameter (mm)	125
Band width (mm)	32
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	8
Bearing seat (mm)	/
Dynamic load capacity (DaN)	105
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	85

## Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	152
Castor hole (mm)	/
Static load capacity (DaN)	125
Structure	Swivel
Version	Axle
Brake	/
Plain axle	12X30
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized