

SERIE 112AM

80B-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 150mm

Material: Non-marking Rubber tyre

Core: Steel

Application field: Industry

Description:

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Rubber tyre

EAN13:/ EAN5:/ Article code:01080SB1500RG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 135 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

| | |
|-----------------------------|-------------------------|
| Diameter (mm) | 150 |
| Band width (mm) | 40 |
| Hub width (mm) | 50 |
| Hub version | Roller bearing |
| Wheel hole (mm) | 15 |
| Bearing seat (mm) | / |
| Dynamic load capacity (DaN) | 135 |
| Colour | Grey |
| Material | Non-marking Rubber tyre |
| Box pieces | / |
| Hardness scale | Shore A |
| Hardness | 80 |

Support data

| | |
|----------------------------|--|
| Plate size (mm) | / |
| Plate hole spacing (mm) | / |
| Plate hole size (mm) | / |
| Offset (mm) | 45 |
| Ground clearance (mm) | 177 |
| Castor hole (mm) | / |
| Static load capacity (DaN) | 170 |
| Structure | Swivel |
| Version | Axle |
| Brake | / |
| Plain axle | 22X50 |
| Stem type | Stem(on request threaded stem) Plain axle |
| Finishing | Galvanized |