

SERIE 112AM

80BIS-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 150mm

Material: Non-marking Rubber tyre

Core: Steel

Application field: Industry

Description:

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Rubber tyre

EAN13:/ **EAN5:/** **Article code:**01080F01500BG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 135 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Plain bore
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	135
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	11X16
Offset (mm)	45
Ground clearance (mm)	176
Castor hole (mm)	/
Static load capacity (DaN)	170
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized