

SERIE 112B-AM

## 90ANT-AM

**AVO - Wheel made of non-marking rubber tyre with steel castor for industry, diameter 150mm ean 13760**

**Material:** Non-marking Rubber tyre

**Core:** Polypropylene

**Scope:** Industry

**Description:**

Wheel with grey no-marking rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Rubber tyre, Stainless steel

**EAN13:**8018793137607

**EAN5:**13760

**Article code:**020900A1500RG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 120 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 83

### Flooring

- Asphalt
- Concrete
- Stoneware

### Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	120
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

### Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	45
Ground clearance (mm)	181
Castor hole (mm)	/
Static load capacity (DaN)	150
Structure	Swivel
Version	Plate with brake
Brake	Front
Stem	/
Stem type	/
Finishing	Galvanized