

SERIE 112AM

80A-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 150mm ean 18944

Material: Non-marking Rubber tyre

Core: Steel

Application field: Industry

Description:

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

In zinc-chromium plated pressed steel, fixed. Assembled with self locking nut.

Product line: Rubber tyre

EAN13: 8018793189446

EAN5: 18944

Article code: 01080A01501RG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 135 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	40
Hub width (mm)	50
Hub version	Roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	135
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	/
Ground clearance (mm)	181
Castor hole (mm)	/
Static load capacity (DaN)	170
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized