

SERIE 16A-AM

## 36B-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 160mm ean 14069

**Material:** Non-marking Rubber tyre

**Core:** Aluminum

**Application field:** Industry

**Description:**

Wheel with elastic grey non-marking rubber tyre 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793140690 **EAN5:**14069 **Article code:**14036B0160GCA



## Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 300 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 68

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

<b>Diameter (mm)</b>	160
<b>Band width (mm)</b>	50
<b>Hub width (mm)</b>	60
<b>Hub version</b>	Ball bearing
<b>Wheel hole (mm)</b>	20
<b>Bearing seat (mm)</b>	47X14
<b>Dynamic load capacity (DaN)</b>	300
<b>Colour</b>	Grey
<b>Material</b>	Non-marking Rubber tyre
<b>Box pieces</b>	/
<b>Hardness scale</b>	Shore A
<b>Hardness</b>	68

## Support data

<b>Plate size (mm)</b>	/
<b>Plate hole spacing (mm)</b>	/
<b>Plate hole size (mm)</b>	/
<b>Offset (mm)</b>	55
<b>Ground clearance (mm)</b>	197
<b>Castor hole (mm)</b>	/
<b>Static load capacity (DaN)</b>	380
<b>Structure</b>	Swivel
<b>Version</b>	Axle
<b>Brake</b>	/
<b>Plain axle</b>	22X50
<b>Stem type</b>	Stem(on request threaded stem) Plain axle
<b>Finishing</b>	Galvanized