

SERIE 16N-AM

## 66A-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 160mm ean 14292

**Material:** Non-marking  
Rubber tyre

**Core:** Polyamide  
6

**Application field:**  
Industry

**Description:**

Wheel with elastic grey non-marking rubber tyre 68 Shore A and Polyamide 6 centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793142922 **EAN5:**14292 **Article code:**00066A0160NCG



### Features

**Minimum temperature:** -20 **Maximum temperature:** 70 **Dynamic load capacity:** 300 DaN  
**Rotation:** Ball bearing **Hardness scale:** Shore A **Hardness:** 68

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 160                     |
| Band width (mm)             | 50                      |
| Hub width (mm)              | 58                      |
| Hub version                 | Ball bearing            |
| Wheel hole (mm)             | 20                      |
| Bearing seat (mm)           | 47X14                   |
| Dynamic load capacity (DaN) | 300                     |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | /                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 68                      |

### Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | 140X110    |
| Plate hole spacing (mm)    | 105X080    |
| Plate hole size (mm)       | 11X16      |
| Offset (mm)                | /          |
| Ground clearance (mm)      | 197        |
| Castor hole (mm)           | /          |
| Static load capacity (DaN) | 380        |
| Structure                  | Fixed      |
| Version                    | /          |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |