

SERIE 112B-AM

90B-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 160mm ean 18054

Material: Non-marking
Rubber tyre

Core:
Polypropylene

Application field:
Industry

Description:

Wheel with grey non-marking rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: Rubber tyre, Stainless steel

EAN13:8018793180542 **EAN5:**18054 **Article code:**02090B01600BG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 140 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 83

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	160
Band width (mm)	40
Hub width (mm)	58
Hub version	Plain bore
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	140
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	194
Castor hole (mm)	/
Static load capacity (DaN)	180
Structure	Swivel
Version	Axle
Brake	/
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized