

SERIE 16A-AM

36B-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 180mm ean 14092

Material: Non-marking Rubber tyre

Core: Aluminum

Application field: Industry

Description:

Wheel with elastic grey non-marking rubber tyre 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793140928

EAN5:14092

Article code:14036B0180GCA



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	180
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	225
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Axle
Brake	/
Plain axle	22X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized