

SERIE 16A-AM

36ANT-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 180mm ean 14097

Material: Non-marking Rubber tyre

Core: Aluminum

Application field: Industry

Description:

Wheel with elastic grey non-marking rubber tyre 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

Product line: Rubber tyre

EAN13:8018793140973

EAN5:14097

Article code:140360A180GCA



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	180
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	225
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized