

SERIE 16A-AM

36ANT-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 200mm ean 14136

Material: Non-marking Rubber tyre **Core:** Aluminum **Scope:** Industry

Description:

Wheel with elastic grey non-marking rubber tyre 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Product line: Rubber tyre

EAN13:8018793141369 **EAN5:**14136 **Article code:**140360A200GCA



Features

Minimum temperature: -20 **Maximum temperature:** 70 **Dynamic load capacity:** 300 DaN
Rotation: Ball bearing **Hardness scale:** Shore A **Hardness:** 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	60
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	55
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized