

SERIE 16N-AM

## 66ANTF-AM

**AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 200mm ean 18903**

**Material:** Non-marking  
Rubber tyre

**Core:** Polyamide  
6

**Application field:**  
Industry

**Description:**

Wheel with elastic grey non-marking rubber tyre 68 Shore A and Polyamide 6 centre. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793189033

**EAN5:**18903

**Article code:**00066FA200NCG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 300 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 68

### Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

### Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 200                     |
| Band width (mm)             | 50                      |
| Hub width (mm)              | 58                      |
| Hub version                 | Ball bearing            |
| Wheel hole (mm)             | 20                      |
| Bearing seat (mm)           | 47X14                   |
| Dynamic load capacity (DaN) | 300                     |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | /                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 68                      |

### Support data

|                            |                      |
|----------------------------|----------------------|
| Plate size (mm)            | /                    |
| Plate hole spacing (mm)    | /                    |
| Plate hole size (mm)       | /                    |
| Offset (mm)                | 55                   |
| Ground clearance (mm)      | 232                  |
| Castor hole (mm)           | 16                   |
| Static load capacity (DaN) | 380                  |
| Structure                  | Swivel               |
| Version                    | Bolt hole with brake |
| Brake                      | Front                |
| Plain axle                 | /                    |
| Stem type                  | /                    |
| Finishing                  | Galvanized           |