Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



SERIE 112AM

80BI-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 225mm

Material: Non-marking Rubber

Core: Steel Application field:

Industry

Description:

tyre

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Rubber tyre

EAN13:/ EAN5:/

Article code:01080BI2250RG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 250 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- ConcreteStoneware

Wheel data

Diameter (mm)	225
Band width (mm)	55
Hub width (mm)	58
Hub version	Roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	1
Dynamic load capacity (DaN)	250
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	1
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	1
Plate hole spacing (mm)	1
Plate hole size (mm)	1
Offset (mm)	55
Ground clearance (mm)	252
Castor hole (mm)	1
Static load capacity (DaN)	300
Structure	Swivel
Version	Axle
Brake	I
Plain axle	40X90
Stem type	Plain axle Stem(on request threaded stem)
Finishing	Galvanized