

SERIE 112AM

80BIS-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 250mm

Material: Non-marking Rubber tyre

Core: Steel

Application field: Industry

Description:

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Rubber tyre

EAN13:/ **EAN5:/** **Article code:**01080F02500RG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 300 DaN

Rotation: Roller bearing

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- Concrete
- Stoneware

Wheel data

Diameter (mm)	250
Band width (mm)	60
Hub width (mm)	75
Hub version	Roller bearing
Wheel hole (mm)	25
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	80

Support data

Plate size (mm)	200X160
Plate hole spacing (mm)	150X115
Plate hole size (mm)	14X26
Offset (mm)	55
Ground clearance (mm)	302
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Swivel
Version	Plate with brake
Brake	Rear
Plain axle	/
Stem type	/
Finishing	Galvanized