

SERIE 139L

# 140L

**AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 75mm ean 22745**

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Industry

**Description:**

Wheel with grey non-marking rubber tyre 85 Shore A and thermoplastic material centre. Hub on central ball bearing with threadguards.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Rubber tyre, Stainless steel

**EAN13:**8018793227452 **EAN5:**22745 **Article code:**0614000075LCG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 60

**Dynamic load capacity:** 75 DaN

**Rotation:** Ball bearing

**Hardness scale:** Shore A

**Hardness:** 85

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 75                      |
| Band width (mm)             | 28                      |
| Hub width (mm)              | 40                      |
| Hub version                 | Ball bearing            |
| Wheel hole (mm)             | 8                       |
| Bearing seat (mm)           | /                       |
| Dynamic load capacity (DaN) | 75                      |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | /                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 85                      |

## Support data

|                            |            |
|----------------------------|------------|
| Plate size (mm)            | 100X085    |
| Plate hole spacing (mm)    | 080X060    |
| Plate hole size (mm)       | 8,5X12     |
| Offset (mm)                | 40         |
| Ground clearance (mm)      | 105        |
| Castor hole (mm)           | /          |
| Static load capacity (DaN) | 96         |
| Structure                  | Swivel     |
| Version                    | Plate      |
| Brake                      | /          |
| Plain axle                 | /          |
| Stem type                  | /          |
| Finishing                  | Galvanized |