

SERIE 112B-AM

## 90ANT-AM

**AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 80mm ean 18033**

**Material:** Non-marking  
Rubber tyre

**Core:**  
Polypropylene

**Application field:**  
Industry

**Description:**

Wheel with grey non-marking rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with plate and front brake. Assembled with self-locking nut and dust cover ring on the balls.

**Product line:** Rubber tyre, Stainless steel

**EAN13:**8018793180337

**EAN5:**18033

**Article code:**020900A0800RG



## Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 50 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 83

## Flooring

- Asphalt
- Concrete
- Stoneware

## Wheel data

|                             |                         |
|-----------------------------|-------------------------|
| Diameter (mm)               | 80                      |
| Band width (mm)             | 30                      |
| Hub width (mm)              | 40                      |
| Hub version                 | Roller bearing          |
| Wheel hole (mm)             | 12                      |
| Bearing seat (mm)           | /                       |
| Dynamic load capacity (DaN) | 50                      |
| Colour                      | Grey                    |
| Material                    | Non-marking Rubber tyre |
| Box pieces                  | /                       |
| Hardness scale              | Shore A                 |
| Hardness                    | 83                      |

## Support data

|                            |                  |
|----------------------------|------------------|
| Plate size (mm)            | 100X085          |
| Plate hole spacing (mm)    | 080X060          |
| Plate hole size (mm)       | 8,5X12           |
| Offset (mm)                | 37               |
| Ground clearance (mm)      | 108              |
| Castor hole (mm)           | /                |
| Static load capacity (DaN) | 70               |
| Structure                  | Swivel           |
| Version                    | Plate with brake |
| Brake                      | Front            |
| Plain axle                 | /                |
| Stem type                  | /                |
| Finishing                  | Galvanized       |