

SERIE 112B-AM

## 90ANTF-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 80mm ean 22363

**Material:** Non-marking Rubber tyre

**Core:** Polypropylene

**Scope:** Industry

**Description:**

Wheel with grey no-marking rubber tyre 83 Shore A with high resistance thermoplastic material centre. Hub on roller bearings or plain bore.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

**Product line:** Rubber tyre, Stainless steel

**EAN13:**8018793223638 **EAN5:**22363 **Article code:**02090FA0800BG



### Features

**Minimum temperature:** -20

**Maximum temperature:** 80

**Dynamic load capacity:** 50 DaN

**Rotation:** Plain bore

**Hardness scale:** Shore A

**Hardness:** 83

### Flooring

- Asphalt
- Concrete
- Stoneware

### Wheel data

Diameter (mm)	80
Band width (mm)	30
Hub width (mm)	40
Hub version	Plain bore
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	50
Colour	Grey
Material	Non-marking Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	83

### Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	106
Castor hole (mm)	12
Static load capacity (DaN)	70
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized