Via XX Settembre, 107 28883 Gravellona Toce (VB) – Italia



www.avo.it +39 0323 86 99 11 export@avo.it

SERIE 112AM

80B-AM

AVO - Wheel with non-marking rubber tyre and steel castor for industry, diameter 80mm ean 23638

Material: Non-marking Rubber tyre

Core:

Application field:

Steel

Industry

Description:

Wheel with no-marking rubber tyre 80 Shore A with zinc-chromium plated pressed steel flanges. Hub on plain bore, roller bearings or shielded ball bearings.

Medium duty castors:

In zinc-chromium plated pressed steel, turning on double rim of balls. Assembled with self locking nut. Dust cover ring on the balls.

Product line: Rubber tyre

EAN13:8018793236386

EAN5:23638

Article code:01080B0080BBG



Features

Minimum temperature: -20

Maximum temperature: 80

Dynamic load capacity: 50 DaN

Rotation: Plain bore

Hardness scale: Shore A

Hardness: 80

Flooring

- Asphalt
- ConcreteStoneware

Wheel data

| Diameter (mm) | 80 |
|-----------------------------|-------------------------|
| Band width (mm) | 25 |
| Hub width (mm) | 40 |
| Hub version | Plain bore |
| Wheel hole (mm) | 12 |
| Bearing seat (mm) | 1 |
| Dynamic load capacity (DaN) | 50 |
| Colour | Grey |
| Material | Non-marking Rubber tyre |
| Box pieces | 1 |
| Hardness scale | Shore A |
| Hardness | 80 |

Support data

| Plate size (mm) | 1 |
|----------------------------|---------------|
| Plate hole spacing (mm) | 1 |
| Plate hole size (mm) | 1 |
| Offset (mm) | 37 |
| Ground clearance (mm) | 106 |
| Castor hole (mm) | 1 |
| Static load capacity (DaN) | 70 |
| Structure | Swivel |
| Version | Axle |
| Brake | 1 |
| Plain axle | 12X50 |
| Stem type | Threaded axle |
| Finishing | Galvanized |