

SERIE 16A-BU

16A-BU

AVO - Wheel with cut-resistant rubber tyre for industry, diameter 100mm ean 16402

Material: Cut-resistant Rubber tyre

Core: Aluminum

Application field: Industry

Description:

Wheel with blue elastic cut-resistant rubber tyre 68 Shore A and aluminium centre. Hub on shielded ball bearings assembled with central spacer.

Product line: Rubber tyre

EAN13:8018793164023

EAN5:16402

Article code:8316AB1510040



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 160 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	100
Band width (mm)	40
Hub width (mm)	40
Hub version	Ball bearing
Wheel hole (mm)	15
Bearing seat (mm)	32X9
Dynamic load capacity (DaN)	160
Colour	Blue
Material	Cut-resistant Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	/
Ground clearance (mm)	/
Castor hole (mm)	/
Static load capacity (DaN)	/
Structure	/
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	/