

SERIE 16NX

66XANTB

AVO - Wheel with cut-resistant rubber tyre and aisi 304 stainless steel castor for industry, diameter 100mm ean 17889

Material: Cut-resistant
Rubber tyre

Core: Polyamide
6

Application field:
Industry

Description:

Blue elastic cut-resistant rubber wheel 68 Shore A with black polyamide 6 centre.
Hub on stainless steel roller bearings.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420,
with stem and front brake. Dust cover ring on the balls.

Product line: Stainless steel

EAN13:8018793178891

EAN5:17889

Article code:00X66BA101NRB



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 150 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Stoneware
- Wood

Wheel data

Diameter (mm)	100
Band width (mm)	36
Hub width (mm)	40
Hub version	Stainless steel roller bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Blue
Material	Cut-resistant Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	37
Ground clearance (mm)	126
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Axle with brake
Brake	Front
Plain axle	20X50
Stem type	Plain axle Stem(on request threaded stem)
Finishing	AISI 304 stainless steel