

SERIE 16NX

66X

AVO - Wheel with cut-resistant rubber tyre and aisi 304 stainless steel castor for industry, diameter 100mm ean 26843

Material: Cut-resistant
Rubber tyre

Core: Polyamide
6

Application field:
Industry

Description:


Blue elastic cut-resistant rubber wheel 68 Shore A with black polyamide 6 centre. Hub on stainless steel roller bearings.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate. Dust cover ring on the balls.

Product line: Stainless steel

EAN13:8018793268431 **EAN5:**26843 **Article code:**00X6600101NCB



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 150 DaN

- Stoneware
- Wood

Rotation: Stainless steel ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

Wheel data

Diameter (mm)	100
Band width (mm)	36
Hub width (mm)	40
Hub version	Stainless steel ball bearing
Wheel hole (mm)	12
Bearing seat (mm)	/
Dynamic load capacity (DaN)	150
Colour	Blue
Material	Cut-resistant Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	37
Ground clearance (mm)	128
Castor hole (mm)	/
Static load capacity (DaN)	190
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel