

SERIE 16NX

66X

AVO - Wheel with cut-resistant rubber tyre and aisi 304 stainless steel castor for industry, diameter 125mm ean 24040

Material: Cut-resistant
Rubber tyre

Core: Polyamide
6

Application field:
Industry

Description:

Blue elastic cut-resistant rubber wheel 68 Shore A with black polyamide 6 centre.
Hub on stainless steel roller bearings.

Medium duty castors:


Made of pressed stainless steel AISI 304, turning on double rim of stainless-steel balls AISI 420, with plate. Dust cover ring on the balls.

Product line: Stainless steel

EAN13:8018793240406

EAN5:24040

Article code:00X66S0126NRB



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 170 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Stoneware
- Wood

Wheel data

Diameter (mm)	125
Band width (mm)	36
Hub width (mm)	50
Hub version	Stainless steel roller bearing
Wheel hole (mm)	15
Bearing seat (mm)	/
Dynamic load capacity (DaN)	170
Colour	Blue
Material	Cut-resistant Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	100X085
Plate hole spacing (mm)	080X060
Plate hole size (mm)	8,5X12
Offset (mm)	42
Ground clearance (mm)	155
Castor hole (mm)	/
Static load capacity (DaN)	220
Structure	Swivel
Version	Plate
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel