

SERIE 16NX

66XF

AVO - Wheel with cut-resistant rubber tyre and aisi 304 stainless steel castor for industry, diameter 160mm ean 19683

Material: Cut-resistant
Rubber tyre

Core: Polyamide
6

Application field:
Industry

Description:

Blue elastic cut-resistant rubber wheel 68 Shore A with black polyamide 6 centre.
Hub on stainless steel roller bearings.

Medium duty castors:

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420,
with bolt hole. Dust cover ring on the balls.

Product line: Stainless steel

EAN13:8018793196833

EAN5:19683

Article code:00X66F0160NRB



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 300 DaN

Rotation: Stainless steel roller bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Stoneware
- Wood

Wheel data

Diameter (mm)	160
Band width (mm)	50
Hub width (mm)	58
Hub version	Stainless steel roller bearing
Wheel hole (mm)	20
Bearing seat (mm)	/
Dynamic load capacity (DaN)	300
Colour	Blue
Material	Cut-resistant Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	194
Castor hole (mm)	16
Static load capacity (DaN)	380
Structure	Swivel
Version	Bolt hole
Brake	/
Plain axle	/
Stem type	/
Finishing	AISI 304 stainless steel