

SERIE 16NX

## 66XANTF

**AVO - Wheel with cut-resistant rubber tyre and aisi 304 stainless steel castor for industry, diameter 80mm ean 20683**

**Material:** Cut-resistant  
Rubber tyre

**Core:** Polyamide  
6

**Application field:**  
Industry

**Description:**

Blue elastic cut-resistant rubber wheel 68 Shore A with black polyamide 6 centre.  
Hub on stainless steel roller bearings.

**Medium duty castors:**

Made of pressed stainless steel AISI 304, turning on double rim of balls AISI 420,  
with bolt hole and front brake. Dust cover ring on the balls.

**Product line:** Stainless steel

**EAN13:** 8018793206839

**EAN5:** 20683

**Article code:** 00X66FA080NRB



## Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 120 DaN

**Rotation:** Stainless steel roller bearing

**Hardness scale:** Shore A

**Hardness:** 68

## Flooring

- Stoneware
- Wood

## Wheel data

|                             |                                |
|-----------------------------|--------------------------------|
| Diameter (mm)               | 80                             |
| Band width (mm)             | 36                             |
| Hub width (mm)              | 40                             |
| Hub version                 | Stainless steel roller bearing |
| Wheel hole (mm)             | 12                             |
| Bearing seat (mm)           | /                              |
| Dynamic load capacity (DaN) | 120                            |
| Colour                      | Blue                           |
| Material                    | Cut-resistant Rubber tyre      |
| Box pieces                  | /                              |
| Hardness scale              | Shore A                        |
| Hardness                    | 68                             |

## Support data

|                            |                          |
|----------------------------|--------------------------|
| Plate size (mm)            | /                        |
| Plate hole spacing (mm)    | /                        |
| Plate hole size (mm)       | /                        |
| Offset (mm)                | 37                       |
| Ground clearance (mm)      | 105                      |
| Castor hole (mm)           | 12                       |
| Static load capacity (DaN) | 150                      |
| Structure                  | Swivel                   |
| Version                    | Bolt hole with brake     |
| Brake                      | Front                    |
| Plain axle                 | /                        |
| Stem type                  | /                        |
| Finishing                  | AISI 304 stainless steel |