

SERIE 16N

66ANTF

AVO - Wheel with cut-resistant rubber tyre and steel castor for industry, diameter 150mm ean 21704

Material: Cut-resistant Rubber tyre

Core: Polyamide 6

Application field: Industry

Description:

Wheel with elastic rubber coating, stain-resistant, cut-resistant, grey or black 68 Shore A and core in Polyamide 6. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with bolt hole and front brake. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793217040

EAN5:21704

Article code:00066FA150NCB



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	150
Band width (mm)	50
Hub width (mm)	58
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Blue
Material	Cut-resistant Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	/
Plate hole spacing (mm)	/
Plate hole size (mm)	/
Offset (mm)	55
Ground clearance (mm)	182
Castor hole (mm)	16
Static load capacity (DaN)	380
Structure	Swivel
Version	Bolt hole with brake
Brake	Front
Plain axle	/
Stem type	/
Finishing	Galvanized