

SERIE 16N

66A

AVO - Wheel with cut-resistant rubber tyre and steel castor for industry, diameter 200mm ean 14316

Material: Cut-resistant Rubber tyre

Core: Polyamide 6

Application field: Industry

Description:

Wheel with elastic rubber coating, stain-resistant, cut-resistant, grey or black 68 Shore A and core in Polyamide 6. Hub on shielded ball bearings assembled with central spacer.

Medium duty castors:

Made of zinc-chromium plated pressed steel, fixed. Assembled with self-locking nut.

Product line: Rubber tyre

EAN13:8018793143165

EAN5:14316

Article code:00066A0200NCB



Features

Minimum temperature: -20

Maximum temperature: 70

Dynamic load capacity: 300 DaN

Rotation: Ball bearing

Hardness scale: Shore A

Hardness: 68

Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

Wheel data

Diameter (mm)	200
Band width (mm)	50
Hub width (mm)	58
Hub version	Ball bearing
Wheel hole (mm)	20
Bearing seat (mm)	47X14
Dynamic load capacity (DaN)	300
Colour	Blue
Material	Cut-resistant Rubber tyre
Box pieces	/
Hardness scale	Shore A
Hardness	68

Support data

Plate size (mm)	140X110
Plate hole spacing (mm)	105X080
Plate hole size (mm)	11X16
Offset (mm)	/
Ground clearance (mm)	235
Castor hole (mm)	/
Static load capacity (DaN)	380
Structure	Fixed
Version	/
Brake	/
Plain axle	/
Stem type	/
Finishing	Galvanized