

SERIE 16N

# 66ANTB

AVO - Wheel with cut-resistant rubber tyre and steel castor for industry, diameter 200mm ean 20741

**Material:** Cut-resistant  
Rubber tyre

**Core:** Polyamide  
6

**Application field:**  
Industry

**Description:**

Wheel with elastic rubber coating, stain-resistant, cut-resistant, grey or black 68 Shore A and core in Polyamide 6. Hub on shielded ball bearings assembled with central spacer.

**Medium duty castors:**

Made of zinc-chromium plated pressed steel, turning on double rim of balls, with stem and front brake. Assembled with self-locking nut.

**Product line:** Rubber tyre

**EAN13:**8018793207416

**EAN5:**20741

**Article code:**00066BA200NRB



## Features

**Minimum temperature:** -20

**Maximum temperature:** 70

**Dynamic load capacity:** 300 DaN

**Rotation:** Roller bearing

**Hardness scale:** Shore A

**Hardness:** 68

## Flooring

- Asphalt
- Concrete
- Grid
- Stoneware

## Wheel data

|                             |                           |
|-----------------------------|---------------------------|
| Diameter (mm)               | 200                       |
| Band width (mm)             | 50                        |
| Hub width (mm)              | 58                        |
| Hub version                 | Roller bearing            |
| Wheel hole (mm)             | 20                        |
| Bearing seat (mm)           | /                         |
| Dynamic load capacity (DaN) | 300                       |
| Colour                      | Blue                      |
| Material                    | Cut-resistant Rubber tyre |
| Box pieces                  | /                         |
| Hardness scale              | Shore A                   |
| Hardness                    | 68                        |

## Support data

|                            |                                           |
|----------------------------|-------------------------------------------|
| Plate size (mm)            | /                                         |
| Plate hole spacing (mm)    | /                                         |
| Plate hole size (mm)       | /                                         |
| Offset (mm)                | 55                                        |
| Ground clearance (mm)      | 232                                       |
| Castor hole (mm)           | /                                         |
| Static load capacity (DaN) | 380                                       |
| Structure                  | Swivel                                    |
| Version                    | Axle with brake                           |
| Brake                      | Front                                     |
| Plain axle                 | 22X50                                     |
| Stem type                  | Plain axle Stem(on request threaded stem) |
| Finishing                  | Galvanized                                |